

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012157 A1

(51) International Patent Classification⁷: **B67D 1/04**, 1/08

(21) International Application Number:
PCT/NL2004/000514

(22) International Filing Date: 15 July 2004 (15.07.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1023969 21 July 2003 (21.07.2003) NL

(71) Applicant (for all designated States except US):
HEINEKEN TECHNICAL SERVICES B.V. [NL/NL];
Burgemeester Smeetsweg 1, NL-2382 PH Zoeterwoude
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PAKKERT, En-
gbert, Hermannes** [NL/NL]; Michiel de Ruiterweg 39,
NL-2628 BA Delft (NL). **INNIKEL, Quintijn** [NL/NL];
Beresteinseweg 76, NL-1217 TK Hilversum (NL).

(74) Agent: **VAN WESTENBRUGGE, Andries**; Nederland-
sch Octrooibureau, Scheveningseweg 82, P.O. Box 29720,
NL-2502 LS The Hague (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: ASSEMBLY FOR DRINK DISPENSER AND CONTAINER PROVIDED WITH A PRESSURE MEDIUM RESER-
VOIR



(57) Abstract: The invention relates to an assembly of a drink dispenser (2) provided with a chamber (4) for accommodating a containing carbonated drink, a lid (5) for closing the chamber, a dispensing head (13) for opening and closing a dispensing line (10) and a container (3) containing carbonated drink provided with a drink dispensing opening (8) and with a dispensing line (10) that connects the drink dispensing opening head, wherein the container is provided with a pressure medium feed opening (21) and with a reservoir (17) with a pressure medium therein which reservoir is provided with a pressure line coupling (20) wherein the lid is provided with a pressure line (22) with, at one end, a reservoir connector (23) for connecting to the pressure line coupling (20) of the reservoir and with, at the end, a pressure medium feed opening (21) of the container, wherein the reservoir connector and the pressure medium feed connector are brought into fluid-tight engagement with the pressure line coupling and the pressure medium feed opening, respectively, by closing the lid.

WO 2005/012157 A1

WO 2005/012157 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Assembly of drink dispenser and container provided with a pressure medium reservoir

The invention relates to an assembly of a drink dispenser provided with a chamber
5 for accommodating a container containing carbonated drink, a lid for closing off the
chamber, a dispensing head for opening and closing a dispensing line and a container
containing carbonated drink provided with a drink dispensing opening and with a
dispensing line that connects the drink dispensing opening to the dispensing head, wherein
the container is provided with a pressure medium feed opening.

10 The invention also relates to a drink dispenser and a container for use in such a
dispenser.

A drink dispenser assembly is disclosed in NL-A 1019054 in the name of the
Applicant. In this publication a container containing carbonated drink, in particular beer, is
described, wherein the beer is packed in a flexible bag, which bag is accommodated in a
15 rigid plastic container. The container is placed in the dispenser, which is provided with a
compressor that is connected to the container via a pressure line to build up pressure in the
space between the flexible bag and the rigid outer container. The use of a compressor in the
dispenser makes this relatively complex, whilst the compressor can give rise to vibration
and an increased noise level.

20 Furthermore, it is known to supply pressure medium, such as CO₂, to containers,
such as metal containers containing whipped cream or cans of beer, by means of a CO₂
cartridge containing CO₂ under high pressure, such as 50 bar and higher. The volume of the
CO₂ cartridge is relatively small and a large proportion of the CO₂ will escape on
connection if the connection is not made quickly and in a sealed manner. The seals for the
25 high-pressure CO₂ cartridges and the pressure regulation thereof are relatively complex.
Furthermore, with the known devices there is no facility for the user to set a regulating
pressure.

A beer keg in which a pressure medium chamber is formed by a cavity in the keg
containing gaseous CO₂ therein is also known from Gebrauchsmusterschrift DE 201 15 158
30 U1. A separate dispensing head that contains a pressure regulator can be connected by the
user to a beer dispensing valve and to a CO₂ feed valve of the beer keg. When the
dispensing head is connected the pressure medium chamber is connected to the volume of
beer in the keg. The pressure regulating element is not indicated in more detail. However, if

manual connection is effected by an inexperienced user, loss of CO₂ from the pressure medium chamber can take place, so that the tap pressure is reduced or as a result of which, in the worst case, only a portion of the contents can be tapped from the beer keg.

One aim of the invention is, therefore to provide an assembly of a drink dispenser
5 and a container containing carbonated drink, for which no external pressure means such as a compressor are needed.

A further aim of the invention is to provide a drink dispenser assembly with which the chamber with carbonated drink therein can be connected in a simple, rapid and reliable manner to a pressure medium reservoir by inexperienced users.

10 A further aim of the invention is to provide a drink dispenser assembly where commercially available reservoirs containing liquid CO₂ under high pressure can be connected in a simple manner and with relatively low losses.

To this end the container of the assembly according to the invention is provided with a pressure medium feed opening and with a reservoir with a pressure medium therein,
15 which reservoir is provided with a pressure line coupling, wherein the lid is provided with a pressure line with, at one end, a reservoir connector for connecting to the pressure line coupling of the reservoir and with, at the other end, a pressure medium feed connector for connecting to the pressure medium feed opening of the container, wherein the reservoir connector and the pressure medium feed connector are brought into fluid-tight engagement
20 with the pressure line coupling and the pressure medium feed opening, respectively, by closing the lid.

When the container is placed in the drink dispenser, the contents of the container are connected to the pressure medium reservoir when the lid is closed, without further intermediate operations on the part of the user. The position of the container relative to the
25 lid is accurately defined, for example, by the use of the positioning cheeks on the container as described in NL-A 1019526 in the name of the Applicant, which application is incorporated herein by reference. Closing the lid produces the connection between the pressure medium reservoir and the container without significant loss of pressure medium. To provide a correct closing action, the lid can be provided with a double closure as
30 described in NL-A 1019054 in the name of the Applicant, which publication is incorporated herein by reference.

In one embodiment according to the invention the pressure line is connected to a pressure regulator for setting a pressure drop between the reservoir connector and the

pressure medium feed connector of the pressure line. In this way the dispenser can be set by the user in such a way that a desired dispensing pressure, for example for tapping beer under high pressure, with a large head, or under low pressure, with less frothing, can be set.

In one embodiment the container is provided with an accommodating cavity with a replaceable container containing CO₂ under a pressure higher than 1 bar therein. The container can contain on (sic) compressed CO₂ or CO₂ adsorbed on carbon under a pressure of approximately 10 bar, as described in NL-A 1012922, or can contain liquid CO₂ under a pressure of more than 50 bar. As a result of the rapid and reliable connection of the pressure line to, on the one hand, the CO₂ cartridge and, on the other hand, the drink chamber when the lid is closed (which lid can hinge, rotate or slide with respect to the chamber), there is little loss of pressure medium, which is advantageous in particular when relatively small volumes of pressure medium under high pressure are used.

In a further preferred embodiment the pressure line is in communication with an expansion chamber located between the reservoir connector and the pressure medium feed connector of the pressure line to reduce the pressure of the CO₂ from the reservoir. As a result, the pressure medium feed connection from the pressure line to the chamber containing the carbonated drink can be a relatively low pressure connection, the sealing of which can be implemented relatively easily. Because of the relatively low pressure, a pressure regulator incorporated between the expansion chamber and the pressure medium feed connector can likewise be of simple and consequently inexpensive construction. Furthermore, when the lid is closed, the CO₂ issuing from the reservoir will move to the expansion chamber, so that loss of pressure medium as a result of leakage into the surroundings is reduced.

The reservoir containing CO₂ can be connected to the container such that it can be removed and can comprise an aerosol container or a metal CO₂ cartridge containing liquid CO₂ accommodated in a cavity in the top wall, bottom wall or side wall of the container.

A few embodiments of an assembly according to the invention will be explained in more detail with reference to the appended drawing. In the drawing:

Fig. 1 shows a diagrammatic side view of an assembly according to the present invention,

Fig. 2 shows an assembly where the lid of the drink dispenser is provided with an expansion chamber, and

Fig. 3 shows a detail, on an enlarged scale, of a connection between reservoir connector and pressure line coupling.

Fig. 1 shows an assembly 1 of a drink dispenser 2 and a container 3 containing carbonated drink. Such an assembly is described in NL-A 1019054 in the name of the Applicant, which is incorporated herein by reference. The drink dispenser 2 has a chamber 4, for accommodating the container through a top surface, and a lid 5 that is connected to the wall of the chamber at hinge 6 such that it can hinge. The container 3 is provided with a dispensing opening 8 that is closed off by a spring-loaded valve 9. A dispensing line 10, which pushes in the spring valve 9, is connected to a tap head 13 by means of which a shut-off valve, which is not shown in more detail, at the end of the dispensing line 10 can be opened and closed via a tap handle 14. The chamber 4 can be cooled by a Peltier cooling element.

An accommodating cavity 16 has been made in the container 3, in which cavity a CO₂ cartridge 17 containing liquid CO₂ is accommodated. This can be connected to the accommodating cavity in the fill line, after or before filling the container 3 with carbonated drink, such as beer, in a manner such that it cannot be released by the user. The CO₂ cartridge is provided with a pressure line coupling in the form of a slim connecting nipple 20. Furthermore, the container 3 is provided with a pressure medium feed opening 21 that can be closed off by a spring-loaded ball valve or by a membrane that can be penetrated.

Furthermore, a pressure line 22 with a reservoir connector 23 for engaging in a gas-tight manner on the nipple 20 of the CO₂ cartridge 17 is accommodated in the lid 5. At the other end the pressure line is provided with a pressure medium feed connector 24, for example in the form of a simple gland and opening in the wall of the container 3. A pressure regulator 5 (sic) is incorporated in the pressure line 5 (sic) so that the reduction in pressure between the CO₂ cartridge 17 and the interior of the container 3 can be set by a user in order to obtain the desired tapping characteristics in the case of beer. The position of the pressure line 22 in the lid 5 and of the CO₂ cartridge 17 are such that when the lid 5 is hinged closed, the reservoir connector 23 and the pressure medium feed connector 24 connect to the CO₂ cartridge 17 and to the pressure medium feed opening 21 in the container, respectively. The CO₂ cartridge is activated by the pressure from the lid, for example by puncturing a seal or by operating a ball valve in the CO₂ cartridge, as shown in Fig. 3.

Fig. 2 shows an embodiment where the pressure line 22 is provided with an expansion chamber 40 which has a volume that, for example, is 10 times greater than the volume of the CO₂ cartridge 17. Instead of a CO₂ cartridge it would also be possible to use a container containing active carbon as described in NL-A 1012922 in the name of the Applicant or an aerosol container known per se.

Fig. 3 shows a pressure line coupling 20 for the reservoir 17. This comprises a spring-loaded ball valve 43 and an accommodating sleeve 44, which have been made in an annular plastic fixing member 45. The fixing member 45 is connected to a top wall 47 of the container 3 via a screw thread 46. As reservoir connector 23, the pressure line 22 has a slim nose 48 that is able to extend into the accommodating sleeve 44 and when pushed down as a consequence of closing of the lid 5 pushes down the ball valve 43 and thus connects the contents of the reservoir 17, via pressure regulating valve 25, to the interior of the container 3. The top surface 47 of the container 3 is provided with a feed opening 21 into which the end section of the pressure line 22 has been pushed via a rubber ring seal 50.

Claims

1. Assembly of a drink dispenser provided with a chamber for accommodating a container containing carbonated drink, a lid for closing off the chamber, a dispensing head
5 for opening and closing a dispensing line and a container containing carbonated drink provided with a drink dispensing opening and with a dispensing line that connects the drink dispensing opening to the dispensing head, wherein the container is provided with a pressure medium feed opening and with a reservoir with a pressure medium therein, which reservoir is provided with a pressure line coupling, wherein the lid is provided with a
10 pressure line with, at one end, a reservoir connector for connecting to the pressure line coupling of the reservoir and with, at the other end, a pressure medium feed connector for connecting to the pressure medium feed opening of the container, wherein the reservoir connector and the pressure medium feed connector are brought into fluid-tight engagement with the pressure line coupling and the pressure medium feed opening, respectively, by
15 closing the lid.
2. Assembly according to Claim 1, wherein the pressure line is connected to a pressure regulator for setting a pressure drop between the reservoir connector and the pressure medium feed connector of the pressure line.
20
3. Assembly according to Claim 1 or 2, wherein the container is provided with an accommodating cavity with a replaceable container containing CO₂ under a pressure higher than 1 bar therein.
- 25 4. Assembly according to Claim 3, wherein the replaceable container contains liquid CO₂.
5. Assembly according to one of the preceding claims, wherein the pressure line is is (sic) communication with an expansion chamber located between the reservoir connector
30 and the pressure medium feed connector of the pressure line to reduce the pressure of the CO₂ from the reservoir.

6. Container for use in an assembly according to one of the preceding claims, comprising a reservoir with a pressure medium therein, which reservoir is provided with a pressure line coupling and with a pressure medium feed opening, wherein the reservoir is connected to the container such that it can be removed.

5



7. Container according to Claim 6, wherein the reservoir contains liquid CO₂.


8. Dispenser for use in an assembly according to one of the preceding claims, comprising a chamber for accommodating a container containing carbonated drink, a lid for closing off the chamber, a dispensing head for opening and closing a dispensing line, wherein the lid is provided with a pressure line with, at one end, a reservoir connector for connecting to a pressure line coupling of the reservoir and with, at the other end, a pressure medium feed connector for connecting to the pressure medium feed of a container, wherein the reservoir connector and the pressure medium feed connector are brought into fluid-tight engagement with the pressure line coupling and the pressure medium feed opening of the container, respectively, by closing the lid when a container has been placed in the dispenser.

10

15

1/2

Fig 1**Fig 2**



Best Available Copy
INTERNATIONAL SEARCH REPORT

International Application No NL2004/000514	
--	--

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B67D1/04 B67D1/08		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 B67D F17C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EP0-Internal, PAJ		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A X A A	US 4 402 429 A (VANDEN DRIESCHJE JEAN R) 6 September 1983 (1983-09-06) column 1, line 57 - line 65; figure 4 ----- PATENT ABSTRACTS OF JAPAN vol. 018, no. 090 (M-1560), 15 February 1994 (1994-02-15) & JP 05 296397 A (NIPPON TANSAN GAS CO LTD), 9 November 1993 (1993-11-09) abstract ----- NL 1 019 054 C (HEINEKEN TECH SERVICES) 31 March 2003 (2003-03-31) cited in the application abstract; figures 1,2 ----- <div style="text-align: center;">-/--</div>	6,7 1,8 6,7 1,8 1,6,8
<div style="display: flex; justify-content: space-between;"> <input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex. </div>		
<div style="display: flex;"> <div style="flex: 1;"> <p>* Special categories of cited documents:</p> <p>*A* document defining the general state of the art which is not considered to be of particular relevance</p> <p>*E* earlier document but published on or after the international filing date</p> <p>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>*O* document referring to an oral disclosure, use, exhibition or other means</p> <p>*P* document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>*G* document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search	Date of mailing of the international search report	
26 October 2004	05/11/2004	
Name and mailing address of the ISA European Patent Office, P.B. 5618 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Wartenhorst, F

Best Available Copy
INTERNATIONAL SEARCH REPORT

International Application No
NL2004/000514

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 1 255 526 A (GERODOLLE E) 10 March 1961 (1961-03-10) page 1, right-hand column, line 36 - page 2, left-hand column, line 1 page 2, right-hand column, line 13 - line 17; figure 1	1,6,8
A	US 5 246 140 A (THIX ANDRE ET AL) 21 September 1993 (1993-09-21)	

INTERNATIONAL SEARCH REPORT

International Application No

NL2004/000514

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4402429	A	06-09-1983	FR 2411798 A1 13-07-1979
		AU 514191 B2 29-01-1981	
		BE 872859 A1 19-06-1979	
		CA 1116565 A1 19-01-1982	
		DE 2852946 A1 21-06-1979	
		DE 7836263 U1 29-03-1979	
		ES 476131 A1 16-05-1979	
		GB 2010977 A ,B 04-07-1979	
		IT 1160339 B 11-03-1987	
		JP 54094115 A 25-07-1979	
		JP 58130997 U 03-09-1983	
		NL 7811901 A 21-06-1979	
JP 05296397	A	09-11-1993	JP 3258701 B2 18-02-2002
NL 1019054	C	31-03-2003	NL 1019054 C2 31-03-2003
		CN 1412105 A 23-04-2003	
		EP 1298088 A1 02-04-2003	
		JP 2003128187 A 08-05-2003	
		US 2003071067 A1 17-04-2003	
FR 1255526	A	10-03-1961	NONE
US 5246140	A	21-09-1993	DK 344188 A 24-12-1989
		AT 147364 T 15-01-1997	
		AU 629225 B2 01-10-1992	
		AU 3857589 A 12-01-1990	
		CA 1335984 C 20-06-1995	
		CN 1039566 A ,B 14-02-1990	
		DD 283979 A5 31-10-1990	
		DE 8907059 U1 27-07-1989	
		DE 68927641 D1 20-02-1997	
		WO 8912599 A1 28-12-1989	
		EP 0422085 A1 17-04-1991	
		ES 2014162 A6 16-06-1990	
		JP 2772089 B2 02-07-1998	
		JP 3505321 T 21-11-1991	
		PT 90945 A ,B 29-12-1989	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.